

UV WASH 1076

UV Blanket and Roller wash suited for NBR and EPDM rubber materials

KEY CHARACTERISTICS

- Very strong cleaning power
- Fogra approved
- Water miscible
- Corrosion inhibited
- Flashpoint: 76 °C
- Suited for both manual and automatic use
- Suited for UV and conventional inks

PACKAGING

1000L IBC
200L metal drum
25L jerrycan

FEATURES AND BENEFITS

Strong ink dissolving power

- Fast acting, less standstills
- Economical in use
- Reduced downtime

Corrosion protected

- No corrosion on press components

Free of naphthenes, aromatic and chlorinated hydrocarbons

- Safer and lower environmental impact

INSTRUCTIONS FOR USE

Blankets: Apply with a moist cleaning rag and remove at one go ink and paper dust from the blanket. Then rub with a moist cloth until the blanket is dry.

Ink rollers: Spray undiluted or mixed with water on the rollers, set the doctor blade.

Automatic systems: Follow the programme instructions.

TRANSPORT & STORAGE

Protect the product from extreme climatic conditions. Do not store at temperatures above 35 °C or below -10 °C. Take the necessary precautions to avoid that accidental leakage pollutes the environment. For details about health and safety, please consult the MSDS.

RECOMMENDED AUXILIARIES

Water leveller: special additive added to the water tank of the washing unit

Version 1.0, state 1/10/2012 - All data contained in this technical information sheet is based upon lab tests and practical experience. The user is aware that user specific circumstances may influence the results. This technical information sheet is made for information purposes only and it does not constitute a warranty or guarantee in relation to the correctness or completeness of the data. Errors, omissions and literal mistakes excepted, subject to modifications at any time. The user acknowledges that the data contained herein is only effective as long as no updated technical information sheet is issued which replaces and supersedes any former version of this technical information sheet.